


JOINSCAN LEDs

2 X 5 mm 3PINs DUAL COLOR CLEAR TYPE LED LAMP	
MODEL NO.	L2550C+
EMITTING COLOR	ORANGE RED / ORANGE RED
DICE	GaAsP/GaP / GaAsP/GaP
LENS	CLEAR TYPE

ABSOLUTE MAXIMUM RATINGS (最大極限值) TA = 25 °C				
PARAMETER		SYMBOL	RATING	UNIT
D1 ORANGE RED POWER DISSIPATION		P AD	40.0	mW
D2 ORANGE RED POWER DISSIPATION		P AD	40.0	mW
DERATING LINEAR FROM 25 °C			0.27	m / °C
D1 ORANGE RED CONTINUOUS FORWARD CURRENT		I AF	20.0	mA
D2 ORANGE RED CONTINUOUS FORWARD CURRENT		I AF	20.0	mA
PEAK FORWARD CURRENT (DUTY CYCLE 1 / 10 , 10KHZ)		I PF	90.0	mA
REVERSE VOLTAGE		V R	5.0	V
OPERATING TEMPERATURE		T OPR	-25 °C TO + 85 °C	
STORAGE TEMPERATURE		T STG	-25 °C TO + 85 °C	
SOLDER TEMPERATURE 1/16 INCH BELOW SEATING PLANE FOR 5 SECONDS AT 230 °C OR 3 SECONDS AT 250 °C				

D1 ORANGE RED ELECTRO - OPTICAL CHARACTERISTICS (電性) TA = 25 °C						
PARAMETER	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
FORWARD VOLTAGE	V F	I F = 20mA	—	1.8	—	V
LUMINOUS INTENSITY	I V	I F = 20mA	—	100	—	mcd
PEAK EMISSION WAVELENGTH	λ P	I F = 20mA	—	635	—	nm
REVERSE CURRENT	I R	VR = 5V	—	—	100	μ A

D2 ORANGE RED ELECTRO - OPTICAL CHARACTERISTICS (電性) TA = 25 °C						
PARAMETER	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
FORWARD VOLTAGE	V F	I F = 20mA	—	1.8	—	V
LUMINOUS INTENSITY	I V	I F = 20mA	—	100	—	mcd
PEAK EMISSION WAVELENGTH	λ P	I F = 20mA	—	635	—	nm
REVERSE CURRENT	I R	VR = 5V	—	—	100	μ A



UNIT : mm
TOLERANCE : ± 0.2 mm
REV : B