






JOINSCAN LEDs

S2.3A 2.3 INCH (57mm) SINGLE DIGIT 69.7 X 47.7 X 12mm




UNIT : mm
TOLERANCE : ±0.2mm


A. A2318 SERIES




B. C2318 SERIES




C. A2317 SERIES




D. C2317 SERIES




E. A2314 SERIES




F. C2314 SERIES



G. A2313 SERIES



H. C2313 SERIES



PIN FUNCTION	COMMON ANODE				COMMON CATHODE				WAVE LENGTH (nm)	IR MAX (uA) VR=5V	VF (V) IF=20mA	LUMINOUS INTENSITY IF=20mA
	A	C	E	G	B	D	F	H				
Emitting COLOR	model no.	model no.	model no.	model no.	model no.	model no.	model no.	model no.				
GaP RED	A2318H	A2317H	A2314H	A2313H	C2318H	C2317H	C2314H	C2313H	695	100	8.8	0.6mcd
GaAsP ORANGE RED	A2318O	A2317O	A2314O	A2313O	C2318O	C2317O	C2314O	C2313O	630	100	8.0	4.0mcd
GaP GREEN	A2318G	A2317G	A2314G	A2313G	C2318G	C2317G	C2314G	C2313G	570	100	8.8	4.5mcd
Gap Yellow	A2318Y	A2317Y	A2314Y	A2313Y	C2318Y	C2317Y	C2314Y	C2313Y	600	100	8.8	4.0mcd
GaAlAs SUPER RED	A2318RS	A2317RS	A2314RS	A2313RS	C2318RS	C2317RS	C2314RS	C2313RS	650	100	7.2	8.0mcd
GaAlAs ULTRA RED												
GaAlAs YELLOW GREEN												
Sic BLUE	A2318SF	A2317SF	A2314SF	A2313SF	C2318SF	C2317SF	C2314SF	C2313SF	465±5	100	14.4	30mcd
ZnSe WHITE												

Model No. -BW BLACK SURFACE WHITE SEGMENT
-BR BLACK SURFACE RED SEGMENT
-GW GRAY SURFACE WHITE SEGMENT

Remark :

1. Typical forward current 10~20mA , MAXimum forward current 25mA
2. Solder Temperature 1.6mm Below Seating plane less 5 seconds at 260°C +5°C -30°C
3. Peak Forward current Per Dice , Duty cycle 1/10 , 10KHZ , MAXimum 120mA
4. Operating Temperature From -25°C to 85°C
5. ROHS COMPLIANT

REV : B